


SUPPORT WITH STEEL OR ELASTOMERIC BRGS.

SUPPORT WITH 1/2" ELASTOMERIC BEARING PAD


VARIES FOR ELASTOMERIC BRGS. SEE STD. 27.7

SIDE VIEW OF GIRDER


DETAIL TYP. AT EACH END



TOP VIEW OF GIRDER




LOCATION OF DRAPED STRANDS




MAXIMUM STIRRUP NUMBER REQUIREMENTS

VALUES SHOWN ARE FOR STIRRUPS FOR 35' SPANS AND A 13'-3" GIRDER SPACING, HS20 LOADING. DESIGN STIRRUPS FOR ALL OTHER CASES, USE #4 BARS AT 1'-9" AS MINIMUM STIRRUP AREA.



SECTION THRU GIRDER



SECTION THRU GIRDER

SHOWING WELDED WIRE FABRIC (WWF) STIRRUPS

DESIGNER NOTES

THE MAX. NUMBER OF DRAPED 0.5"φ STRANDS IS 8.

SPECIFY CONCRETE STRENGTH AS REQUIRED BY DESIGN FROM A MINIMUM OF 6,000 PSI TO A MAX. OF 8,000 PSI. USE ONLY 0.5"φ STRAND FOR THE DRAPED PATTERN. USE 0.6"φ FOR THE STRAIGHT PATTERN.

GENERAL NOTES

THESE NOTES APPLY TO ALL GIRDERS.

THE GIRDERS SHALL BE PROVIDED WITH A SUITABLE LIFTING DEVICE FOR HANDLING AND ERECTING THE GIRDERS. ALL GIRDERS SHALL BE CAST FULL LENGTH AS SHOWN.

STRANDS SHALL BE FLUSH WITH END OF GIRDER. ENDS OF STRANDS SHALL BE PAINTED WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. THIS APPLIES ONLY TO THOSE ENDS OF GIRDERS THAT ARE FINALLY EXPOSED.

TOP OF GIRDER TO BE ROUGH FLOATED AND BROOMED TRANSVERSELY FOR BONDING TO THE SLAB, EXCEPT THE OUTSIDE 2" OF GIRDER, WHICH SHALL BE TROWEL FINISHED.


SPACING SHOWN FOR #4 STIRRUPS IS FOR GRADE 60 REINFORCEMENT. IF THE FABRICATOR WANTS TO BUILD A BAR STEEL CAGE BY WELDING LONGITUDINAL REINFORCEMENT TO THE #4 STIRRUPS, TWO OPTIONS ARE AVAILABLE:

1. USE ASTM A706, GRADE 60 REINFORCEMENT AND THE STIRRUP SPACING AS SHOWN ON THE PLANS.

2. USE ASTM A615, GRADE 40 REINFORCEMENT AND A MODIFIED STIRRUP SPACING SUBMITTED TO AND APPROVED BY THE STRUCTURES DEVELOPMENT SECTION.

AN ALTERNATE EQUIVALENT OF WELDED WIRE FABRIC (WWF) MAY BE SUBSTITUTED FOR THE STIRRUP REINFORCEMENT SHOWN, UPON APPROVAL OF THE STRUCTURES DEVELOPMENT SECTION. (608)266-8494

WELDED WIRE FABRIC SHALL CONFORM TO THE REQUIREMENTS OF ASTM A497.



DETAIL A

28" PRETENSIONED GIRDER DETAILS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: *Stanley W. Woods*

DATE:
7-03